

**FEEL THE HEAT!**

## HighBack Seat Installation Instructions

Part # 15-1000	HighBack Seat for RZR 900, 800 & 570 Models (fits 2 & 4 seaters)	Black
Part # 15-1002	HighBack GT Seat for RZR 900, 800 & 570 Models (fits 2 & 4 seaters)	Black
Part # 15-1003	HighBack XL Seat for RZR 900, 800 & 570 Models (fits 2 & 4 seaters)	Black

Congratulations on your purchase of a DragonFire HighBack seat for Polaris RZR 900, 800 & 570 models. Designed specifically for the RZR platform, these seats come in multiple sizes and styles to suit your needs. Providing unmatched comfort, support, style and quality, these HighBack's are a world better than the OEM seats in more ways than one! Please see the detailed installation instructions below for reference and Feel the Heat in your new seat setup!

*\*All HighBack Seats are designed to mount directly to the factory seat base. For the ultimate combination, check out the DragonFire H.D. Aluminum Seat Base - <http://www.dragonfireracing.com/product/1070/hd-aluminum-seat-base-for-rzr> and 4-Point Harness Restraints - <http://www.dragonfireracing.com/category/9/safety> which work in combination with HighBack seats and are available separately.*

### **WARNING**

- Read and understand these instructions before installing product
- This product does not provide roll over protection
- Ensure mounting hardware is securely fastened prior to use of seat
- Do not use product if there is any sign of damage

Tools Required
T27 Torx Bit
½" Socket & Ratchet

### Disclaimer

Off road activities can be hazardous and could lead to injury, dismemberment, paralysis and death. No warranty of representation is made as to the products ability to protect the user from any injury or death. The user assumes that risk. The acceptance and /or use of this merchandise purchased from DragonFire by the customer hereby shall release DragonFire from any and all liability pertaining to the use of such merchandise.

**Step 1:** Place vehicle on a flat and level surface. Place gear selector in park and remove keys from the ignition.

**Step 2:** Remove seat and seat base from vehicle by pulling up on the release handle behind seat, and lifting the seat out.

**Step 3:** With factory seat removed from vehicle, flip upside down and place on the ground so that the factory seat pan is facing upward. Remove 4 factory seat pan



mounting screws using T27 Torx Bit. Lift seat pan off of factory seat frame and set aside. (See Figure A) Retain all hardware to be reused.

**Step 4:** Place HighBack seat upside down on ground and apply factory or aftermarket seat pan on the bottom of seat frame. Make sure that the latch is at the back of the seat. Using slotted holes on factory seat pan, slide seat either forward or backwards to reach desired seat adjustment. Once desired positioning is achieved, secure seat base to frame by reinstalling the 4 mounting screws and hardware removed in step 3 and torque to factory specifications. (See Figure B)



**Step 5:** For 2 seat models and the rear seats on 4 seat models, attach the ring connected to pull-cord nylon strap on the back of seat HighBack Seat, to the seat base release latch handle. Some seat handles may require drilling a larger hole to accept ring. This will allow for easy disengagement of latch with pull-cord strap when seats are installed.

**Step 6:** Install seat back into vehicle making sure it latches in place to complete the installation process. Repeat process for other factory seats being replaced with HighBack's. Time to ride and enjoy!

***ProTip: Periodically check all hardware and re-tighten if needed.***

***For further assistance please contact us at [customerservice@dragonfireracing.com](mailto:customerservice@dragonfireracing.com) or 1-800-708-9803***



Dragonfire Racing